

## DECLARTAION OF PERFORMANCE

Number	91/2022	
Date of issue	12.12.2022	
	Page 1 of 2	

1. Unique identification code of the product-type:

The three-layer membrane for waterproofing AlphaProPlus

2. Intended use/es:

Sheet used in wall construction or in or under floors or ground slabs to prevent liquid water under hydrostatic pressure passing from the ground into the internal environment or from one section of the structure to another.

3. Manufacturer:

Alpha Dam Sp. z o.o. Dębowa Łąka 45 87-207 Dębowa Łąka 45

4. System/s of AVCP

System 2+ System 3 (Reaction to fire)

5. Harmonised standard:

EN 13967:2012 Flexible sheets for waterproofing – Plastic and rubber damp proof sheets including plastic and rubber basement tanking sheet – Definitions and characteristics

Notified body/ies: 1434, 1454 Certification body/ies: 1434

Polish Testing and Certification Center S.A., Testing and Certification Branch in Gdańsk conducted an inspection of factory and factory production control and inspection surveillance, assessment and evaluation of factory production control system 2 + and issued Certificate of Factory Production Control No 1434-CPR-0257



## DECLARTAION OF PERFORMANCE

Number	91/2022	
Date of issue	12.12.2022	
	Page 2 of 2	

## 6. Declared performance/s:

Essential characteristic	Unit	Performance
Reaction on fire	class	Е
Watertightness (60 kPa)	-	meets requirements
Tear resistance: - in transverse direction: - in longitudinal direction:	N N	≥ 270 ≥ 300
Joint shearing strength: - Longitudinal overlapping - Transverse overlapping	N/50 mm	≥ 150 ≥ 130
Resistance to impact	mm	≥ 450
Tensile properties: Maximum strength: - in longitudinal direction: - in transverse direction: Elongation: - in longitudinal direction: - in transverse direction	N/50mm N/50mm % %	≥ 450 ≥ 350 ≥ 350 ≥ 350
Resistance to static loading	kg	≥ 20
Durability after artificial ageing (60 kPa)	-	meets requirements
Durability after alkali resistance (60 kPa)	-	meets requirements
Dangerous substance	-	NPD

7. The performance of the product identified above is in conformity with the set of declared performance. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Proxy Iwona Majek

Dębowa Łąka, 12 December 20222