

1. Unique identification code of the product-type:

EPDM elastomeric membrane for vertical and horizontal damp proofing of facade joints and opening joinery in the construction sector – AlphaFacade OUT

2. Intended use/es:

The purpose of damp proof courses is to prevent water rising up a wall from ground, water moving from one part of a wall to another and to deflect water from an inner wall of a cavity wall construction to the exterior of the building

3. Manufacturer:

Alpha Dam Sp. z o.o.
Dębowa Łąka 45
87-207 Dębowa Łąka 45

4. Systems/s of AVCP:

System 3
System 4 (Reaction to fire)

5. Harmonised standard:

EN 14909:2012 Flexible sheets for waterproofing – Plastic and rubber damp proof courses – Definitions and characteristics

Notified body/ies: 1434, 154

6. Declared performance/s:

Essential characteristics	Unit	Performance
Reaction to fire	class	F
Watertightness (to 2 kPa)		Meet requirements
Resistance to impact (method B)	mm	≥ 800
Resistance to low temperature	°C	≤ -40
Durability after artificial ageing	-	Meet requirements
Durability after alkali resistance	-	Meet requirements
Dangerous substance	-	NPD

7. The performance of the product identified above is in conformity with the set of declared performance. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:



Quality Manager Iwona Majek
Dębowa Łąka, 11 June 2024